

RUT906

4G LTE RS232/RS485 ROUTER

Cellular 4G router for industrial IoT applications, supporting serial interfaces RS232 and RS485, MQTT, BACnet, I/Os, Ethernet, and more. This cellular router is equipped with GNSS and failsafe features such as Dual SIM, auto-failover, and backup WAN.



CONNECTIVITY

4G LTE (Cat 4), 3G, 2G

DUAL SIM

Auto-failover, backup WAN, and more switching scenarios

INTERFACES & PROTOCOLS

Serial interfaces (RS232 & RS485), MQTT, BACnet, OPC UA, I/Os, Ethernet, and more

GNSS

NTRIP, location services and time synchronization



RMS

REMOTE MANAGEMENT SYSTEM

COMPATIBLE WITH RUT906

MANAGEMENT

ALERTS

CONFIGURATION

ACCESS

FOTA

KEY FEATURES

Ikonic Technology Limited
 +44(0)1706 360 000
 www.ikonic.com

HARDWARE

| | |
|------------------------|---|
| Mobile | 4G (LTE) – Cat 4 up to 150 Mbps, 3G – Up to 42 Mbps, 2G – Up to 236.8 kbps |
| CPU | Mediatek, 580 MHz, MIPS 24KEc |
| Memory | 128 MB, DDR2 |
| Storage | 16 MB, SPI Flash |
| Powering options | 4-pin industrial DC power socket, 9 - 30 VDC |
| SIM | 2 x SIM slots (Mini SIM - 2FF), 1.8 V/3 V, external SIM holders, eSIM (Optional) |
| SD Card | Micro SD (internal) |
| Antenna connectors | 2 x SMA for LTE, 2 x RP-SMA for Wi-Fi, 1 x SMA for GNSS |
| Ethernet | 4 x 10/100 Ethernet ports: 1 x WAN (configurable as LAN), 3 x LAN |
| Wi-Fi | IEEE 802.11b/g/n, Access Point (AP), Station (STA) |
| GNSS | GPS, GLONASS, BeiDou, Galileo and QZSS |
| Inputs/Outputs | 2 x Inputs and 2 x Outputs on 10-pin industrial socket, 1 x Digital input and 1 x Digital output on 4-pin power connector |
| Serial | 1 x RS232, 1 x RS485 |
| Other | 1 x USB host |
| Status LEDs | 1 x bi-color connection status, 5 x Mobile connection strength, 4 x ETH status, 1 x Power |
| Operating temperature | -40 °C to 75 °C |
| Housing | Aluminium housing, plastic panels |
| Dimensions (W x H x D) | 109.5 x 50 x 100 mm |
| Weight | 295 g |

SOFTWARE

| | |
|--------------------------------|--|
| Operating system | RutOS (OpenWrt based Linux OS) |
| Mobile features | Auto APN, Band lock, SIM switch, Operator black/white list, Data/SMS limits |
| Network features | Routing, Failover, Firewall, DHCP, DDNS, QoS / SQM, Load Balancing, VoIP passthrough, Connection monitoring, SSHFS |
| Monitoring and Management | WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, BACnet, DNP3, OPC UA, MODBUS, RMS |
| VPN and tunneling | OpenVPN, IPsec, GRE, PPTP, L2TP, L2TPv3, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard, Tinc |
| Cloud solutions | RMS, FOTA, Azure IoT Hub, Cumulocity - Cloud of Things, ThingWorx |
| Wireless Connectivity Features | Fast roaming (802.11r), Relayd |
| Hotspot | External/Internal Radius, SMS OTP, MAC authentication, Walled Garden |
| GNSS | NMEA forwarding, NTRIP, AVL, Geofencing |

FRONT VIEW

BACK VIEW

