


**REQUEST A QUOTE TODAY** 

Ikonic Technology Limited +44(0)1706 360 000 www.ikonic.com



Copyright © 2025, TELTONIKA. Specifications and information given in this document are subject to change by TELTONIKA without prior notice.

## 

## **KEY FEATURES**

Ikonic Technology Limited +44(0)1706 360 000 www.ikonic.com

## HARDWARE

Power supply	2-pin industrial DC power socket, 9 - 30 VDC
Power consumption	Idle: 0.3 W / Max: 0.9 W
Status LEDs	1 x Power LED, 10 x LAN status LEDs
Ethernet	5 x RJ45 ports, 10/100 Mbps, compliance with IEEE 802.3, IEEE 802.3u, 802.3az, IEEE802.3x (Flow control) standards, supports auto MDI/MDIX crossover, Auto-Negotiation function
Ingress protection rating	IP30
Operating temperature	-40 °C to 75 °C
Housing	Anodized aluminum housing and panels
Dimensions	113.1 x 27.4 x 80.5 mm
Weight	146.5 g
Installation	Integrated DIN rail bracket, wall mounting (additional kit needed), flat surface placement

## PERFORMANCE SPECIFICATIONS

Bandwidth (Non-blocking)	1 Gbps
MAC address table size	2K entries
Jumbo frame support	2048 bytes
Switch Processing Scheme	Store-and-Forward

